



KRAMER
on the safe side



5065T

Telescopic wheel loader

The compact telescopic wheel loader.

The Kramer 5065T is equipped with the Kramer quick hitch system and the telescopic loading system allows for more reach and stacking height. Due to the undivided frame and all-wheel steering, the constant payload and stability are fully available with this telescopic wheel loader. With a stacking height of up to 4.0 m, the model is also ideal for loading vehicles.

Safety: The back tilt angle limitation of 45° at maximum lift height protects the operator and machine from unintentional material loss.

Cost Reduction: The efficient high-pressure traction drive ensures low operating costs and high thrust.

Loading system: The optimal design of the loading system ensures the best visibility of the attachments and the quick-change plate.

Compact dimensions: The low overall height of less than 2.5 m and the narrow vehicle width of less than 1.65 m enable easy and cost-effective transport of the telescopic wheel loader.

Unbeatable maneuverability: The realization of a turning radius of only 2,900 mm (outer edge of tire) through 2 x 38° steering angle.

Technical Data

| | | | |
|----------------------------------|-----------------------|---|-----------|
| Exhaust after-treatment | DOC / DPF | Lift capacity (max.) | 32.5 kN |
| Engine manufacturer | Yanmar | Tank capacity for fuel | 60 l |
| Drive output | 34.3 kW | Tank capacity for hydraulic oil | 58 l |
| Displacement | 2,190 cm ³ | Travel speed Standard | 0-20 km/h |
| Drive output | 46 PS | Travel speed Option 1 | 0-30 km/h |
| Bucket content (standard bucket) | 0.65 m ³ | Work hydraulics discharge volume (max.) | 56 l/min |
| Operating weight | 3,500 - 4,600 kg | Work hydraulics working pressure (max.) | 240 bar |
| Tipping load (standard bucket) | 2,500 kg | Kinematics type | Z |
| Tipping load (pallet fork) | 2,060 kg | Steering angle max. | 38 Grad |
| Payload (S=1.25) | 1,650 kg | | |

Dimensions

| | | |
|----|------------------------------|----------|
| A1 | Total length | 5,350 mm |
| B1 | Wheel base center | 2,000 mm |
| D5 | Height with cab | 2,470 mm |
| H1 | Load-over height / retracted | 3,160 mm |
| H2 | Load-over height / extended | 4,010 mm |
| I1 | Dumping height / retracted | 2,650 mm |
| I2 | Dumping height / extended | 3,500 mm |
| J1 | Dumping width / retracted | 560 mm |
| J2 | Dumping width / extended | 810 mm |
| L1 | Total width | 1,595 mm |
| M1 | Ground clearance | 280 mm |
| O1 | Steering angle | 38 ° |
| P1 | Swing angle | 8 ° |
| Y1 | Bucket width | 1,650 mm |
| Z1 | Stacking height / retracted | 3,180 mm |
| Z2 | Stacking height / extended | 4,030 mm |