



KRAMER
on the safe side

5095 Wheel Loader

The down-to-earth powerhouse.

The 5095 machine impresses with its dynamic all-wheel drive and high payload. The bucket volume of 0.95 m³ to 1.5 m³ with low overall height distinguishes the machine in this size class. The efficient high-pressure travel drive enables high thrust forces. In addition, the optional high-speed gear offers further versatile applications.

Bucket volume: The bucket volume of 0.95 m³ to 1.5 m³ with a headroom of less than 2.5 m distinguishes the machine in this size class.

Speed: The 5095 can be equipped with the 30 km/h fast gear.

Long loading system: An extended mast is available, which makes the machine more flexible in terms of reach and pile height.

Exhaust gas stage V: Exhaust gas aftertreatment takes place through DOC and DPF.

Technical Data

Exhaust after-treatment	DOC / DPF	Payload (S=1.25)	2,350 kg
Engine manufacturer	Kohler	Lift capacity (max.)	42.8 kN
Drive output	55.4 kW	Tank capacity for fuel	75 l
Displacement	2,482 cm ³	Tank capacity for hydraulic oil	50 l
Drive output	75 PS	Travel speed Standard	0-20 km/h
Bucket content (standard bucket)	0.85 m ³	Travel speed Option 1	0-30 km/h
Operating weight	4,714 - 4,800 kg	Work hydraulics discharge volume (max.)	68,4 l/min
Tipping load (standard bucket)	3,800 kg	Work hydraulics working pressure (max.)	240 bar
Tipping load (pallet fork)	2,900 kg	Kinematics type	P
Payload (max.)	1,710 kg	Steering angle max.	40 Grad

Dimensions

A1	Total length	4,640 mm
B1	Wheel base center	2,020 mm
D5	Height with cab	2,480 mm
H1	Load-over height	3,210 mm
I1	Dumping height	2,680 mm
J1	Dumping width	580 mm
L1	Total width	1,740 mm
M1	Ground clearance	330 mm
O1	Steering angle	40 °
P1	Swing angle	22 °
Z1	Stacking height	3,150 mm
Y1	Bucket width	1,950 mm